

TEMPERATURE CONTROLS BASIC FOR ALL MODELS OF BOILERS



BRIDGE *
Receiver for Wireless version



> OSCAR W (ON/OFF PROGRAMMABLE THERMOSTAT)

- **Weekly** programming, max 6 periods a day
- Preset standard program, which can be completely customised
- Manual mode available
- Relay with voltage-free contact (24 to 230 V)
- Operated by 2xAA type batteries
- Extra functions for all models: **pump anti-seize, pre-heating, holiday, week-end, party**
- Phone contact input, for remote boiler switch on/off
- Model **RF** features **wireless** transmission to boiler's control board

COMPATIBILITY

Opentherm-ready boilers /
ON-OFF operated boilers / SUN P N

CODE	DESCRIPTION
013110XA	OSCAR W - WIRED PROGRAMMABLE THERMOSTAT WEEKLY PROGRAMMING
013111XA	OSCAR W RF - WIRELESS PROGRAMMABLE THERMOSTAT WEEKLY PROGRAMMING

TEMPERATURE CONTROLS EVOLVED ONLY FOR BOILERS THAT CAN BE COMBINED WITH REMOTE CONTROL




AX5200SQ

> CASCADE CONTROLLER

- this can manage a cascade of one to five boilers
- the request to switch on the individual modules is made through a direct communication bus with the individual boilers
- the operating power of each boiler is managed directly by the regulator according to the load required by the system
- through the outdoor probe it can manage the flow temperature compensation of the heating system
- the kit consists of a regulator, an external temperature probe and a probe for the system flow temperature

CODE	DESCRIPTION
1KWMH18A	CASCADE MODULE CONTROL UNIT



FZ4 B

> FZ4 B ZONING CONTROLLER

- board for systems with zones (max 3) two of which are mixed and one is direct, operating in combination with both modulating control timers and ON/OFF programmable thermostats
- it manages delivery temperatures that are sliding and differentiated between the zones

CODE	DESCRIPTION
013013X0	FZ4 B BOARD FOR SYSTEMS WITH ZONES

TEMPERATURE CONTROLS EVOLVED ONLY FOR BOILERS THAT CAN BE COMBINED WITH REMOTE CONTROL



Control



RF/Wifi receiver



> CONNECT wifi modulating remote control with programmable thermostat function

- Remote control to **manage comfort in the home even from Smartphone**.
- Connection to the home WiFi network for internet access through the supplied RF/WiFi receiver.
- **CONNECT APP** available for switching the boiler on and off and managing home comfort for heating/DHW via remote control from Smartphone (iOS and Android)
- With the APP it is possible to remotely control boilers in «evolved» mode via the OpenTherm connection and in «basic» mode through the ON/OFF connection.
- Modulating regulation of the delivery temperature with ambient climatic compensation, for boilers connected via OpenTherm («evolved»).
- Modulating regulation of the delivery temperature with climatic compensation through external temperature (detected by the internet or by an optional outdoor probe), for boilers connected via OpenTherm («evolved»).
- **It improves the average seasonal efficiency in room heating by +4%** if combined with boilers via the OpenTherm connection.
- Room regulation with ON/OFF programmable thermostat operation, for boilers connected via on/off («basic»)
- Weekly hourly programming in 30-minute intervals (via APP CONNECT).
- **Reading of the external temperature from the internet** (via APP CONNECT) or from an optional outdoor probe (if installed)
- Alarm display also through CONNECT APP
- Operating mode: Off, Holiday, Automatic, Manual.
- Three modifiable temperature levels: Comfort, Economy, Antifrost
- Battery status indicator (also from APP CONNECT)
- Supplied material: 2 x 1.5V AAA batteries, table stand, 230 Vac power supply unit, boiler connection USB cable, set of wall fixing screws, user manual.

CODE	DESCRIPTION
013010XA	WIFI MODULATING REMOTE CONTROL WITH PROGRAMMABLE THERMOSTAT FUNCTION



BRIDGE *

Receiver for Wireless version

> ROMEO W (MODULATING REMOTE CONTROL)

- **weekly** programming, max 6 periods per day
- heating delivery and domestic hot water temperature settings
- external temperature display and possibility of working at sliding temperature with outdoor probe (optional)
- modulation of the delivery temperature according to the room temperature
- boiler on - off - reset
- phone contact input
- Models: **W** wired - **W RF** with Wireless transmitter
- **A+ SYSTEM**: **Romeo** and the **outdoor probe**, combined with a **Ferrol boiler** with seasonal efficiency η_s 94%, constitute a heating system with **labelling A+** (scale from G to A+++)

CODE	DESCRIPTION
013100XA	ROMEO W - WIRED REMOTE CONTROL WEEKLY PROGRAMMING
013101XA	ROMEO W RF - WIRELESS REMOTE CONTROL WEEKLY PROGRAMMING

